

# DECK LIGHT - MODEL NUMBER - PAR 30 FLOOD - 15mm

**underwater lights limited™**

Manufacturers of the Original **underwater lights™**  
Brand Marine Lighting Products since 1991

## DESCRIPTION

The **PAR 30 Adjustable flood light** with bolted bezel is used for exterior flood lighting onto areas such as decks or masts.

The fitting accommodates a 15mm thick borosilicate glass for installation into areas open to heavy weather and requires an insert to be welded onto the superstructure. The inserts are manufactured in Aluminium 5083 (part number S23061-A) or in 316 Stainless Steel (Part number S23062-A).

The light is available with a 150w metal halide bulb - max 150w - or with a halogen bulb - max 75w - The electronic ballast for the metal halide fitting is remote from the lamp. The maximum distance from the ballast to the lamp is 10 meters.

The light has been tested for water tightness (front face only) to IP 56.

## TECHNICAL SPECIFICATION

**Lamp type - 150w Metal Halide. 75w Halogen**

**Voltage -12v or 24v - 120v 230v transformer**

**IP Rating - IP 56**

**Glass lens finish - Clear or Frosted ( 15mm)**

**Bezel Finish - Bolted 316 Stainless Steel**

**Insert - 4/15mm bezel Alu or S.Steel**

**Ballast -S00800-A-V1 - Transformer - 120/230V**

### NOTE-

#### -Installation Instruction-

The hole cut-out is 178mm with insert.

The light is supplied with one meter of 3 core cable. Longer cable can be fitted on request.

#### Part no-

S23014- (150w Metal Halide) with 150w Ballast ( S00800-A-V1) and 15mm S.S. bolted bezel.

S23016 -V5/V6 for Halogen 75w max 12v/24v- with 15 mm glass and S.S bolted bezel.

S23016-V2 Halogen with 12v/230v transformer- with 15 mm glass and S.S bolted bezel.

S23016-V3 Halogen with 12v/120v transformer- with 15 mm glass and S.S bolted bezel.

For additional information please visit our web site.

**PAR 30 WITH BOLTED BEZEL  
AND 15MM GLASS**



**Dimension with insert  
for 15mm glass.**

